



33' EXTENDABLE BRIDGEMASTER

- Made in the U.S.A.
- **2** 11,200lbs
- 65,000lb GVWR
- Spring Ride Suspension
- Extends to 41' to carry 20' ISO

- **INTRODUCING** the 33' Cheetah Extendable
- Bridgemaster Chassis. Expanding to 41' allows for
 - transportation of a heavy loaded 20' ISO container (up to 24 metric tons).

CONTACT

MATT FLOWER
Director of Sales

717.492.2665

MFlower@PennStroLeasing.com

"Your Capacity Problem Solving Partner"

Headquarters: 1976 Auction Road Manheim, PA 17545 Shippensburg Branch: 15 Hershey Road Shippensburg, PA 17257 Visit us at PennStroLeasing.com





33' EXTENDABLE BRIDGEMASTER

Overall Length	Closed - 33'; Open - 41'
Overall Width	96" over bolsters; 102" over tires
Kingpin Setting	15" from front of chassis
Weight	11,200 lbs. +/- 3%
Suspension	Spring Ride
Axles	Three Axles; 53-1/2"
Tires	11Rx22.5
Wheels	8.25" x 22.5 hub piloted tubeless
Brakes	Three tank, three valve system; 30/30 brake chambers
Upper Coupler	1/4" thick pick-up plate; 18" behind king pin
Main Frame	Fabricated I-beam with 1/2" x 6" Grade 80 flanges and 1/4" web
Cross Members	All cross-members are formed from 7-guage steel
Bolsters	Front: 1/4" wall x 6" x 8" tube with 1/2" end plates; Rear: 5/16" wall x 6" x 8" tube with 1/2" end plates
Twist Locks	Meets ISO standards and requirements
Landing Gear	Two speed, AAR approved, squared leg. 50,000lb lift capacity and 140,000lb static load capacity.
Lights	Flange mounted LED light
Electrical	12 volt; 7 Way split pin receptacle plug; modular wiring harness

"Your Capacity Problem Solving Partner"

Headquarters: 1976 Auction Road Manheim, PA 17545 Secondary Location: 15 Hershey Road Shippensburg, PA 17257 Visit us at PennStroLeasing.com